







ROSH,FCC,CE,CCC,Energy Star,BIS

THIN CLIENT LIBERATE THE POWER OF YOUR PC WITH MULTI-USER COMPUTING

Features:	Specification:	E-FL300
 High compatible Support with all Operating Systems. 	System	
	Processor	Cortex A53,RK3328,1.5Ghz Quad-Core 64bit
 Support printers with using of USB redirection software. High resolution of Video quality after installing video improvement software RDP Acceleration software. 	Protocol	RDP8.1/10/10.6
	System Memory	1GB
	Storage Memory	8GB
	Display Resolution	1920x1200 @60Hz
 Smart management software 1-TC-Manager can realize the functions that the host can restart or power off the users remotely. 2- Share the host and chat with users flexible. 	Operating System	Windows 7/8.1/10/11,Linux OS
		Windows MultiPoint Server 2008 R2/2012 R2/2016 R2
	Interface	
	Power Adapter	5VDC
	Output Current(max)	2.5A or 3A
	Output Ports	1xVGA,1xHDMI, 4xUSB2.0, 1xUSB3.0, 1xSpk Port
	Input Ports	1xDC Port,1xRJ45 Port, 1xMIC Port
	High Speed Network Port	10/100/1000Mbps
	Appearance	
	Product Size	102x102x28mm
	Product Weight	Net: 143g
We recommend to add 256MB per additional Thin Client terminal.	Mounting Kit	Mounting Plate
	Performance	
Host PC Host PC Switch THIN CLIENT 1 Host PC THIN CLIENT 40	Operating Temperature	0 ~ 35°C
	Operating Humidity (Rh)	10% ~90~(non-condensing)
	Operation Voltage Range	100~240VAC
	Rated Line Frequency	50~50Hz
	Cooling	Fan-less Convection

Regulatory